

Product description

Our Wil-Seal EverSeal is a high-quality water-based sealer, formulated to mitigate moisture Exchange between dry wood and the environment, preventing splits and deformation of wood exposed to moderately humid environments. For best results, coat the wood surface for at least 3 days before installation. Wil-Seal EverSeal is available in color white.

Properties

Viscosity (sec. CF#4 at 25°C)	55 ± 5
Density (lbs/gal at 25°C)	8.0 ± 0.2
Solids in weight (% , 10 min 150°C)	41 ± 2
pH (25°C)	9 ± 1
Color	White

Application

Our product Wil-Seal Everseal must be agitated for at least 30 minutes before use, until the product is completely homogenous. Do not incorporate air in this process. The product can be applied with a spray system, brush or roller, at a thickness not below 10 mils. If wood will be exposed to severe conditions, apply several successive coat of the product. This product was developed to be used without dilution, and transferring of the product is not recommended; however, if needed, contact Tapel Willamette Inc.S.A Technical Service for further assistance. Use warm water and soap to clean up application tools.

Storage

This product must be stored indoors between 5 and 35°C with a maximum relative humidity of 85%. The product has a useful life of 3 month from manufacturing date.

Health and Safety

There are no unusual health hazards associated with this product. However, it is recommend wearing protective clothing, personal protection equipment and adequate ventilation. Before using this product, it is recommended to read the information available regarding hazards, appropriate use and handling of this product. Refer to the SDS before using this product.