

## MAINTENANCE AND CLEANING FOR PRISM TFL PANELS

In order to maintain the life and appearance of your Prism thermally fused laminate and Prism WRM panels, please follow these guidelines:

- ✓ **After installing the panels, remove adhesives with paint lacquer thinner or contact adhesive solvent.**  
Continued use of solvent cleaners is not recommended.
- ✓ **Thermally fused melamine finished panels may be easily cleaned using a mild, non-abrasive, all-purpose cleaner and a soft cloth.**  
Coffee, tea or other difficult stains may be removed using a mild household detergent or a paste of baking soda and water (note: 10-20 strokes should remove most stains, excessive force or scrubbing may damage the surface)
- ✓ **Harsh chemicals or abrasive materials should not be used.**  
Should the surface come in contact with drain, toilet or oven cleaner immediately remove the chemical, rinse thoroughly and wipe dry.  
Abrasives such as scouring pads or gritty cleansers may permanently dull and/or scratch the surface and result in future staining.
- ✓ **Protect the surface from hot or sharp objects.**  
Do not place hot cookware, dishes or objects onto the surface. Knives and other sharp objects used directly on the surface can also be damaging. Protect surfaces from heat with an insulating pad or trivet, and from sharp objects with a chopping block or counter protector.
- ✓ **Do not compromise surfaces with InCopper® antimicrobial protection.**  
Along with the guidelines above, avoid frequent or excessive rubbing, and do not apply paint, varnish or furniture oils/polish which can damage the Prism TFL finish and compromise antimicrobial protection.